

Stainless Steel Dry Gauges

Applications:

Stainless steel gauges provide the corrosion resistance and durability of a permanently sealed gauge. Designed for severe service applications.

¼" lower mount

2½" face

PSI Range	Fig. Inter.	Minor Grad.	Part #	Price/E
0-15	3	.2	GSS15	\$104.15
0-30	5	.5	GSS30	104.15
0-60	10	1	GSS60	104.15
0-100	20	2	GSS100	104.15
0-160	20	2	GSS160	104.15
0-200	50	5	GSS200	104.15
0-300	50	5	GSS300	104.15
0-400	100	10	GSS400	104.15
0-600	100	10	GSS600	104.15
0-1000	200	20	GSS1000	104.15
0-1500	300	20	GSS1500	115.30
0-2000	500	50	GSS2000	115.30
0-3000	500	50	GSS3000	115.30
0-5000	1000	100	GSS5000	115.30
0-10000	2000	200	GSS10000	119.00

Features:

- 2-1-2% accuracy
- 304 stainless steel case with stainless crimp ring
- polycarbonate window
- ¼" lower mount stainless connector
- 316 stainless bourdon tube and socket
- temperature range: -40°F to 140°F



GSS100

¼" lower mount

3½" face

PSI Range	Fig. Inter.	Minor Grad.	Part #	Price/E
0-15	3	.5	GSS15-4	\$164.00
0-30	5	.5	GSS30-4	164.00
0-60	10	1	GSS60-4	164.00
0-100	20	2	GSS100-4	164.00
0-160	20	2	GSS160-4	164.00
0-200	40	5	GSS200-4	164.00
0-300	50	5	GSS300-4	164.00
0-400	50	10	GSS400-4	164.00
0-600	100	10	GSS600-4	164.00
0-1000	200	10	GSS1000-4	164.00
0-1500	200	20	GSS1500-4	164.00
0-2000	400	20	GSS2000-4	164.00
0-3000	500	50	GSS3000-4	164.00
0-5000	1000	100	GSS5000-4	164.00
0-10000	2000	200	GSS10000-4	179.50

Features:

- 3-2-3% accuracy
- 316 series stainless solid back case
- polycarbonate window
- ¼" lower mount stainless connector
- 316 stainless bourdon tube and socket, polyester segment
- temperature range: -40°F to 140°F



GSS160-4

Stainless Steel Liquid Filled Gauges

Applications:

Stainless steel gauges provides the corrosion resistance and durability of a permanently sealed gauge. Designed for severe service applications.

2½" face ¼" lower mount

PSI Range	Fig. Inter.	Minor Grad.	Part #	Price/E
0-15	3	.2	GLSS15	\$112.40
0-30	5	.5	GLSS30	112.40
0-60	10	1	GLSS60	112.40
0-100	20	2	GLSS100	112.40
0-160	20	2	GLSS160	112.40
0-200	50	5	GLSS200	112.40
0-300	50	5	GLSS300	112.40
0-400	100	10	GLSS400	112.40
0-600	100	10	GLSS600	112.40
0-1000	200	20	GLSS1000	112.40
0-1500	300	20	GLSS1500	112.40
0-2000	500	50	GLSS2000	112.40
0-3000	500	50	GLSS3000	112.40
0-5000	1000	100	GLSS5000	112.40
0-10000	2000	200	GLSS10000	112.40

Features:

- 2-1-2% accuracy
- 2½" 304 series stainless case with stainless crimp ring
- polycarbonate window
- ¼" lower mount stainless connector
- 304 stainless case with stainless crimp ring
- glycerin filled
- temperature range: -4°F to 140°F



GLSS1500