

Grease Whip Hose Assemblies

Features:

- for use with hand grease guns only
- one piece brass crimp couplings
- 1/8"-27 male NPT thread, solid base
- US manufactured 3/16" ID hose - exceeds SAE 100R1-AT
- strain relief spring option is available as a special, consult Dixon™ for pricing
- working pressure: **3000 PSI**



Part #	Assembly Length	Price/E
<i>GWH-0800</i>	8"	\$12.14
<i>GWH-1200</i>	12"	14.25
NEW <i>GWH1200R</i> ¹	12"	19.40
<i>GWH-1800</i>	18"	17.91
NEW <i>GWH1800R</i> ¹	18"	23.08
<i>GWH-2400</i>	24"	21.55
<i>GWH-3600</i>	36"	28.80
<i>GWH-4800</i>	48"	36.09
<i>GWH-6000</i>	60"	43.27

¹ retail packaging

Grease Whip Hose Fittings

Features:

- male and female fittings are designed to be crimped on **grease hose couplers**



Zinc Plated Steel Part #	Description	Price/E	Pkg Qty
<i>GWH-C</i>	grease hose coupler with ball check - valved shutoff	\$8.15	25
<i>GWHC-FF</i>	full flow grease hose coupler	8.15	25

male NPT thread - chamfered base



Brass Part #	Description	Price/E	Pkg Qty
<i>001-0055</i>	1/8"-27 male NPT thread, drilled and chamfered base	\$3.30	100

male NPT thread - solid base



Brass Part #	Description	Price/E	Pkg Qty
<i>001-0260</i>	1/8"-27 male NPT thread, solid base	\$2.69	100

female NPT thread



Brass Part #	Description	Price/E	Pkg Qty
<i>001-0860</i>	1/8"-27 female NPT thread	\$5.20	100

Grease Whip Fittings



Zinc Plated Steel Part #	Threads	Description	Overall Length	Thread Length	Hex	Price/E	Pkg Qty
<i>GWHZ000</i>	1/8-27 NPT	straight	.660	.260	.430	\$0.81	100
<i>GWHZ045</i>	1/8-27 NPT	45°	.860	.280	.430	1.11	100
<i>GWHZ090</i>	1/8-27 NPT	90°	.830	.310	.430	1.12	100
<i>GWHZ400</i>	1/4-28 tapered SAE-LT	straight	.530	.200	.312	0.63	100
<i>GWHZ445</i>	1/4-28 tapered SAE-LT	45°	.800	.200	.375	1.13	100
<i>GWHZ490</i>	1/4-28 tapered SAE-LT	90°	1.20	.200	.375	1.13	100