Applications:

Clear PVC Tubing

domestic

Clear PVC Tubing is designed to be used with standard shank fittings in low pressure liquid and pneumatic applications.

- for non-critical hospital use such as suction and draining made from non-toxic ingredients conforming to FDA and 3A standards
- shipped in individually boxed bundles, sold only in lengths shown below
- maximum temperature: 175°F

Size		Working Pressure	Length	PVC	
ID	OD	(PSI) @ 72°F	Lengui	Part #	Price/E
3/16"	5/16"	55	100'	CL0305	\$46.00
1/4"	3/8"	55	100'	CL0406	62.75
1/4"	1/2"	70	100'	CL0408	117.00
5/16"	7/16"	50	100'	CL0507	63.75
3/8"	1/2"	40	100'	CL0608	72.25
3/8"	5/8"	65	100'	CL0610	153.00
1/2"	5/8"	30	100'	CL0810	101.00
1/2"	3/4"	45	100'	CL0812	184.00
5/8"	7/8"	40	100'	CL1014	250.00
3/4"	1"	35	100'	CL1216	258.00
1"	1-1/4"	28	100'	CL1620	340.00
1-1/4"	1-3/4"	45	50'	CL2028-50	520.00
1-1/2"	2"	40	50'	CL2432-50	545.00
	-				



imported

Features:

- temperature range: 14°F to 149°F
- shipped in bundles wrapped with PVC film, sold only in lengths shown below

Size		Working Pressure	Longth	PVC	
ID	OD	(PSI) @ 72°F	Length	Part #	Price/E
1/4"	3/8"	50	100'	ICL0406	\$25.50
3/8"	1/2"	35	100'	ICL0608	35.45
1/2"	5/8"	35	100'	ICL0810	46.30
1/2"	3/4"	50	100'	ICL0812	100.90
3/4"	1"	35	100'	ICL1216	143.50
1"	1¼"	30	100'	ICL1620	178.55
1½"	2"	15	50'	ICL2432	290.55

Clear PVC Braided Tubing

domestic

Applications:

Clear PVC Braided Tubing is designed to be used in low pressure liquid and pneumatic applications.

- high grade tensile strength polyester yarn reinforcement temperature range: 27°F to 150°F
- shipped in coils, sold only in lengths shown below

		<u> </u>			
Size		Working Pressure	Length	PVC	
ID	OD	(PSI) @ 72°F	Lengui	Part #	Price/E
3/16"	.394	315	300'	BR0306	\$300.00
1/4"	.435	315	300'	BR0446	360.00
3/8"	.625	265	300'	BR0609	651.50
1/2"	.728	215	300'	BR0812	560.00
5/8"	.906	200	300'	BR1014	830.00
3/4"	1.024	150	300'	BR1218	820.00
1"	1.375	185	200'	BR1621	1420.00
1-1/4"	1.732	110	100'	BR2027	890.00
1-1/2"	1.950	90	100'	BR2431	1775.00



imported

Features:

- for various machine tools and the transportation of chemicals temperature range: 14°F to 149°F
- shipped in bundles wrapped with PVC film, sold only in lengths shown below

		11	, ,		
Size		Working Pressure	Longth	PVC	
ID	OD	(PSI) @ 72°F	Length	Part #	Price/E
1/4"	1/2"	142	300'	IBR0446	\$191.00
3/8"	5/8"	114	300'	IBR0609	246.25
1/2"	3/4"	100	300'	IBR0812	310.00
3/4"	1-1/16"	71	300'	IBR1218	661.30
1"	1-5/16"	71	200'	IBR1621	513.10