

## Dixon Northline Hydrant Gate Valves with Speed Handle

**Application:**

- protects fire hydrants from damage that can occur if they are used for throttling

**Features:**

- full 2½" waterway
- anodized throughout - minimum thickness 0.001"
- test pressure: **250 PSI**, working pressure: **100 PSI** at 70°F (21°C)



Inlet Female Swivel	Outlet Male	Alum. Alloy, 356-T6 Part #	Price	Wt. Lbs.
2½" NPSH	2½" NPSH	<b>AHGV250S</b>	<b>\$656.25</b>	5.0
2½" NST (NH)	2½" NST (NH)	<b>AHGV250F</b>	<b>656.25</b>	5.0
2½" CSA	2½" CSA	<b>AHGV250C</b>	<b>656.25</b>	5.0
2½" BAT	2½" BAT	<b>AHGV250B</b>	<b>656.25</b>	5.0
2½" WCT	2½" WCT	<b>AHGV250W</b>	<b>656.25</b>	5.0
2½" QST	2½" QST	<b>AHGV250Q</b>	<b>656.25</b>	5.0
2½" NS1	2½" NS1	<b>AHGV250NS</b>	<b>656.25</b>	5.0

**Replacement Parts**

Description	Part #	Price	Wt. Lbs.
handwheel and knob	<b>HGV-HDWHL</b>	<b>\$154.55</b>	1.0
knob only	<b>HGV-KNOB</b>	<b>76.40</b>	.25

## Global Hydrant Gate Valves with Speed Handle

**Application:**

- protects fire hydrants from damage that can occur if they are used for throttling

**Features:**

- pin lug swivel, non-rising stem, aluminum speed handle
- non-metallic seal
- maximum operating pressure: **175 PSI** (water only) at 70°F (21°C)



Inlet Female NST (NH)	Outlet Male NST (NH)	Aluminum Part #	Price	Wt. Lbs.
2½"	2½"	<b>AHGV250F-I</b>	<b>\$394.30</b>	3.75

**Replacement Part**

Description	Aluminum Part #	Price	Wt. Lbs.
speed handle	<b>AHGV250F-H</b>	<b>\$65.00</b>	1.0