## Male x Grooved Adapters with Internal Lugs



Feature:

• allows the conversion of a female NPT valve inlet to connect to grooved piping

Male NPT	Grooved Size	Length	<i>Brass</i> Part #	Price
21⁄2"	21⁄2"	2-3/64"	VMIL250	\$41.70
4"	4"	2-3/64"	VMIL400	66.50

# Male x Male Adapters with Internal Lugs



### Feature:

allows the conversion of a female NPT valve inlet to connect to hose



Male NPT	Male NH (NST)	Length	<i>Brass</i> Part #	Price
21⁄2"	21⁄2"	1-29/64"	DMIL250F	\$36.10
21⁄2"	3"	1-31/64"	DMIL2530F	45.25

• All adapters are made to approved Dixon<sup>™</sup> specifications.

# **Straight Globe Valves**

#### Features:

- ideal for wet and combination systems
- used with a fire hose rack assembly, or as a fire department outlet connection
- aluminum handwheel
- maximum operating pressure: 300 PSI at 70°F (21°C)

_	Female x Male				
	Inlet Female	Outlet Male	Cast Brass Part #	Price/E	
	1½" NPT	1½" NST (NH)	SGV150F	\$374.05	
	21⁄2" NPT	21⁄2" NST (NH)	SGV250F	566.70	

## Female x Female

Inlet Female NPT	Outlet Female NPT	Cast Brass Part #	Price/E
11⁄2"	11⁄2"	SGVF150	\$448.20
21⁄2"	21⁄2"	SGVF250	635.35

## Dimensions



Size	A	В	C (closed)	D (open)
1½"	2-3/8"	4-3/4"	7-1/4"	8"
2½"	3-9/32"	6-9/16"	7-3/8"	8-1/8"



Ρ