

Single Clapper Siamese Connections

Features:

- single swing clapper with (2) pin lug swivel inlets
- provides 500 GPM minimum to supplement the fire protection as an auxiliary inlet connection to the water supply (250 GPM minimum per inlet)
- design provides unobstructed waterway
- exposed Fire Department Connections (FDC) provide an economical method of satisfying local fire codes
- branding: Auto-Sprk
- finishes: -P polished or -C polished chrome plated
- maximum operating pressure: **250 PSI** at 70°F (21°C)
- replacement swivels can be ordered on page 581




Feature:

- U/L listed and FM approved

Outlet Female NPT	(2) Inlets Female	Cast Brass Part #	Price
4"	2½" NST (NH)	SCS4025F	\$539.25
4"	2½" NYFD	SCS4025NYFD	595.90
4"	2½" NST (NH)	ISCS4025F ¹	224.25

¹ imported

Dimensions



Size	A	B	C
4" x 2½" x 2½"	5⅞"	9"	6-1/16"

- dimensions match SCS4025F and SCS4025NYFD




Feature:

- U/L listed

Outlet Female NPT	(2) Inlets Female	Cast Brass Part #	Price
4"	2½" NST (NH)	90SCS4025F	\$603.05
4"	2½" NYFD	90SCS4025NYFD	719.95
4"	2½" NST (NH)	90ISCS4025F ¹	239.40

¹ imported

Dimensions



Size	A	B
4" x 2½" x 2½"	6⅞"	9⅞"

- dimensions match 90SCS4025F, and 90SCS4025NYFD

P