

Synthetic Single Jacket Mill Hose

Application:

- Used in open end water discharge applications only. Not intended for fire fighting service.



Features:

- outer construction: single jacket, all polyester
- tube construction: black, PVC rubber
- rated pressure: **250 PSI** at ambient temperature (70°F)
- working pressure: **112 PSI** at ambient temperature (70°F)
- Consult Dixon for pricing and availability on 75' lengths and other threads and configurations.



Uncoupled

Size	Bowl	Length	Part #	Price/E
1"	1-1/4"	50'	M10-50UC	\$91.55
1"	1-1/4"	100'	M10-100UC	183.00
1½"	1-11/16"	25'	M15-25UC	50.45
1½"	1-11/16"	50'	M15-50UC	101.00
1½"	1-11/16"	100'	M15-100UC	202.00
2"	2-3/8"	25'	M20-25UC	58.30
2"	2-3/8"	50'	M20-50UC	117.00
2"	2-3/8"	100'	M20-100UC	234.00
2½"	2-11/16"	25'	M25-25UC	80.75
2½"	2-11/16"	50'	M25-50UC	161.00
2½"	2-11/16"	100'	M25-100UC	323.00
3"	3-3/8"	25'	M30-25UC	96.60
3"	3-3/8"	50'	M30-50UC	193.00
3"	3-3/8"	100'	M30-100UC	387.00
4"	4-3/8"	25'	M40-25UC	147.00
4"	4-3/8"	50'	M40-50UC	294.00
4"	4-3/8"	100'	M40-100UC	588.00
6"	6-3/8"	25'	M60-25UC	259.00
6"	6-3/8"	50'	M60-50UC	518.00

Coupled with female and male expansion ring couplings



P

Size	Length	Rocker Lug Aluminum NPSH RAS	Price	Rocker Lug Aluminum NST (NH) RAF	Price	Rocker Lug Aluminum MNPT x MNPT RAT	Price	Rocker Lug Aluminum CT RA ¹	Price
1½"	50'	M15-50RAS	\$194.75	M15-50RAF	\$194.75	M15-50RAT	\$194.75	---	---
1½"	100'	M15100RAS	284.40	M15100RAF	284.40	M15100RAT	284.40	---	---
2"	50'	M20-50RAS	284.40	---	---	M20-50RAT	284.40	---	---
2"	100'	M20100RAS	383.30	---	---	M20100RAT	383.30	---	---
2½"	25'	M25-25RAS	216.40	M25-25RAF	216.40	---	---	M25-25RA¹	POR
2½"	50'	M25-50RAS	315.30	M25-50RAF	315.30	M25-50RAT	327.65	M25-50RA¹	POR
2½"	100'	M25100RAS	474.50	M25100RAF	474.50	M25100RAT	489.95	M25100RA¹	POR

¹ Customer Thread (must specify) refer to legend on page 566

Consult Dixon for pricing and availability for any of the following features:

- 75' lengths
- other threads and configurations