1/4 Turn Forestry Adapters

Features:

- maximum operating pressure: 300 PSI at ambient temperature (70°F)
- adapters have a common quarter turn sexless head (a 1½" QT fitting will mate with a ¾" QT or 1" QT)
- replacement gaskets: QTG-F \$7.00

Thread	Forged Aluminum Male Part #	Price/E	Forged Aluminum Female Part #	Price/E
¾" GHT	QTM75GHT-F	\$74.25	QTF75GHT-F	\$79.80
1" NPSH	QTM100S-F	71.05	QTF100S-F	89.10
1" NPT	QTM100T-F	71.05	QTF100T-F	89.10
11/2" NST (NH)	QTM150F-F	42.45	QTF150F-F	57.60
1½" NPT	QTM150T-F	68.40	QTF150T-F	81.90
11/2" NPSH	QTM150S-F	54.55	QTF150S-F	57.60





Quick-Connect Forestry Expansion Ring Couplings

Feature:

sold in sets of (2) with expansion ring

Hose Size	Bowl Size	Forged Aluminum Part #	Price/E
1½"	1-11/16"	QTX150-F	\$95.30



Forestry Hose Expansion Ring Rocker Lug Couplings

Features:

- lugs on female only
- working pressure: 270 PSI
- under no circumstances should the fittings be used beyond the working pressure of the hose



- Assembled hose should be hydrostatically proof tested before use, and thereafter in accordance with NFPA 1962.
- special tooling is required to attach these couplings to hose
- shipped with expansion rings, a swivel washer and tail washers
- for females or males only, consult Dixon™ for pricing and availability

Hose Size	Thread Type	Bowl Size	<i>Aluminum</i> Part #	Price/E
1"	NPSH	1-3/16"	EF11118	\$70.30
1"	NPSH	1-1/4"	EF11125	70.30
1½"	NH (NST)	1-13/16"	EF16168F	91.15
1½"	NH (NST)	2-11/16"	EF16175F	91.15



D